

Cable Kit Basic PLUS

Kit with heating cable, manual thermostat and a variety of mounting accessories.

The heating cable is Ø3 mm. The floor heating can therefore be established in only 5 mm building height.
Min. 5 °C cable temperature during instalation.

The manual HC30-15 thermostat is simple and easy to operate.



Technical Data



Voltage	230 V ~ 50 Hz
Cable diameter	Ø3 mm
Insulation inner sheath	Teflon, FEP
Authorisation	CE, SEMKO, BEAB
Cable buildup	2 conductors + ground shield
Ground shield	Tinned copper
Outer sheath	PVC
Max. temp. on cable	90 °C
Building height	Min. 5 mm
Warranty	Thermostat 3 years / Cabel 15 years
Standard	EN60335-2-96
Resistance tolerance	- 5 % / +10 %
Length tolerance	+/- 2 %

Cable Kit Basic PLUS

Item	Type	Description	Power	Current	Resistance
39410130	CKB-30-0130	Ø3 mm Cable Kit Basic PLUS 11.3 m, HC30-15	130 W	0.6 A	407 Ω
39410200	CKB-30-0200	Ø3 mm Cable Kit Basic PLUS 16.5 m, HC30-15	200 W	0.9 A	264 Ω
39410290	CKB-30-0290	Ø3 mm Cable Kit Basic PLUS 23.5 m HC30-15	290 W	1.3 A	183 Ω
39410420	CKB-30-0420	Ø3 mm Cable Kit Basic PLUS 36.0 m, HC30-15	420 W	1.8 A	126 Ω
39410490	CKB-30-0480	Ø3 mm Cable Kit Basic PLUS 39.0 m, HC30-15	480 W	2.1 A	109 Ω
39410580	CKB-30-0570	Ø3 mm Cable Kit Basic PLUS 47.0 m, HC30-15	570 W	2.5 A	92 Ω
39410670	CKB-30-0660	Ø3 mm Cable Kit Basic PLUS 57.0 m, HC30-15	660 W	2.9 A	80 Ω
39410800	CKB-30-0790	Ø3 mm Cable Kit Basic PLUS 68.0 m, HC30-15	790 W	3.5 A	67 Ω
39410960	CKB-30-0960	Ø3 mm Cable Kit Basic PLUS 79.0 m, HC30-15	960 W	4.2 A	55 Ω
39411050	CKB-30-1050	Ø3 mm Cable Kit Basic PLUS 87.0 m, HC30-15	1050 W	4.6 A	50 Ω
39411190	CKB-30-1190	Ø3 mm Cable Kit Basic PLUS 99.0 m, HC30-15	1190 W	5.2 A	45 Ω
39411340	CKB-30-1330	Ø3 mm Cable Kit Basic PLUS 112.0 m, HC30-15	1330 W	5.8 A	40 Ω
39411600	CKB-30-1590	Ø3 mm Cable Kit Basic PLUS 133.0 m, HC30-15	1590 W	6.9 A	33 Ω
39411740	CKB-30-1740	Ø3 mm Cable Kit Basic PLUS 145.0 m, HC30-15	1740 W	7.6 A	30 Ω
39412000	CKB-30-1990	Ø3 mm Cable Kit Basic PLUS 166.0 m, HC30-15	1990 W	8.7 A	27 Ω
39412140	CKB-30-2130	Ø3 mm Cable Kit Basic PLUS 177.0 m, HC30-15	2130 W	9.3 A	25 Ω